Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Quality Engineering Test Report

Model : SLW05L-12 DC-DC Single Output Converter
V1 : 12V / 41.7~417mA

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2%~+2% (Max)	I/P:5VDC O/P:50% LOAD Ta:25℃	+0.5%	P
2	RIPPLE & NOISE	100mVp-p (Max)	I/P:5VDC O/P:FULL LOAD Ta:25℃	15mV	P
3	LINE REGULATION	-0.2%~+0.2% (Max)	I/P:4.5VDC~9VDC O/P:FULL LOAD Ta:25℃	-0%~+0%	P
4	LOAD REGULATION	-0.5%~+0.5% (Max)	I/P:5VDC O/P:MIN~FULL LOAD Ta:25℃	-0%~+0%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	DC VOLTAGE RANGE	4.5VDC~9VDC (Typ)	I/P:TESTING O/P:FULL LOAD Ta:25℃	3.5V~9V	P
2	EFFICIENCY	70% (Typ)	I/P:5VDC O/P:FULL LOAD Ta:25℃	71.0%	P
3	DC CURRENT	1420mA (Max)	I/P:5VDC O/P:FULL LOAD Ta:25℃	1417mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	YES	I/P:5VDC O/P:TESTING Ta:25℃	151% Hiccup Mode Reset Auto Recovery	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:5VDC O/P:FULL LOAD Ta:25℃	NO DAMAGE Hiccup Mode Reset Auto Recovery	P

Quality Engineering Test Report

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN：39HRS I/P:5VDC O/P:FULL LOAD Ta=25℃			P

Position	P/N	TEMP Ta=25℃
CASE	SLW05L-12	41.2℃

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1KVDC/min	I/P-O/P:1KVDC/min Ta:25℃	I/P-O/P:0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500VDC Ta:25℃	I/P-O/P:30GΩ NO DAMAGE	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2003.9.16	SLW05L-12	PASS	FRANK.CHEN	MAX LIN